
	ITTC – Recommended Procedures		7.5 – 02 05 – 05 Page 1 of 4	
	Testing and Extrapolation Methods High Speed Marine Vehicles Manoeuvrability Evaluation and Documentation of HSMV		Effective Date 2002	Revision 01

CONTENTS

1. PURPOSE OF PROCEDURE
2. DESCRIPTION OF PROCEDURE
3. PARAMETERS
4. DOCUMENTATION
5. REFERENCES

Updated by	Approved
Manoeuvring Committee of 23rd ITTC	23rd ITTC 2002
Date	Date 2002

	ITTC – Recommended Procedures	7.5 – 02 05 – 05 Page 2 of 4	
	Testing and Extrapolation Methods High Speed Marine Vehicles Manoeuvrability Evaluation and Documentation of HSMV	Effective Date 2002	Revision 01

Manoeuvrability Evaluation and Documentation of HSMV

1. PURPOSE OF PROCEDURE

These procedures address the manoeuvrability of High Speed Marine Vehicles (HSMV), especially those not governed by the IMO Interim Standards for ship manoeuvrability. The class is comprised of a large variety of hull shapes, such as monohull, which may be semi-planing or planing, catamaran, trimaran, hydrofoil, and surface-effect and hovercraft.

Usually, the common element of HSMV is the high Froude number. The ABS (1997) rule formula is:

$$V \text{ (knots)} \geq 2.36 L \text{ (ft)}^{1/2}$$

corresponding to a Froude number of 0.7.

Besides the definition based on Froude number, other criteria exist, based on the absolute speed value and as it relates to the environment of operation:

- ratio of harbour manoeuvring speed to service speed;
- ratio of service speed to service speed of other ships;
- rating on a scale incorporating human controllability, or traffic density.

In accordance with the definition of high speed by the 21st ITTC (1996) High Speed Marine Vehicles Committee, based on (but slightly modified) the IMO (1995) Code of

Safety, the following criteria must both be satisfied:

$$V \text{ (m/s)} \geq 3.7 V_c^{1/6}$$

$$V \text{ (kn)} \geq 25 \text{ kn}$$


The critical displacement is $V_c = 1764 \text{ m}^3$; hence smaller vessels will meet the first condition travelling at less than 25 knots, while large vessels may not meet it even if they are travelling more than 25 knots.

All vessels above 100 meters in length are subject to the IMO Interim Standards for ship manoeuvrability; hence, the manoeuvring performance of these vessels will be assessed through these standards. However, many HSMV are below 100 meters in length and do not qualify. Also, most HSMV are passenger ships, for which safety may be an issue when subjecting them to the standard manoeuvring tests, especially at high speed.

2. DESCRIPTION OF PROCEDURE

Evaluation of HSMV manoeuvring can be performed by different methods:

- free sailing model tests
- simulation model based on captive model tests
- full scale tests
- CFD

	ITTC – Recommended Procedures	7.5 – 02 05 – 05 Page 3 of 4	
	Testing and Extrapolation Methods High Speed Marine Vehicles Manoeuvrability Evaluation and Documentation of HSMV	Effective Date 2002	Revision 01

For some of these methods, appropriate procedures exist or are in development (see ITTC Quality Manual, 1999, 2002: Captive Model Test Procedure, Free Sailing Model Test Procedure, Manoeuvring Trial Procedure). In general, these procedures are applicable to HSMVs, but some specific aspects require special treatment:


- At high speed, HSMV may exhibit strong dynamic effects during manoeuvring, e.g. yaw-roll coupling.
- Manoeuvring properties vary greatly over the speed range of HSMVs (low-speed, take-off, cruising; transient phases of dynamic lift vehicles).
- High speed induces a higher frequency of encounter with obstacles in a cluttered environment, requiring special attention to emergency manoeuvres, including crash stops, turning and collision avoidance.
- Dynamic properties of sensors, actuators, and the control system play a significant role in HSMV manoeuvring because the physical response of the vessel is very fast.
- Course keeping ability in a seaway must be assessed, with particular emphasis on broaching in following and stern quartering seas.
- HSMV often reduce speed:
 - a. in cluttered seaways or in channels and harbours to reduce the risk of collision;
 - b. in rough seas to avoid excessive dynamic loads;
 - c. to reduce wake wash effects when near shore or in enclosed areas. Hence these ships must satisfy some manoeuvring requirements at reduced speed as well.

- Depending on operational requirements, the HSMV may also require manoeuvring performance at very low and zero speeds. The effects of wind at low speed should be checked.
- Foil-assisted boat stability in calm and rough seas, i.e. motion control systems.

As a means of reference for assessing their manoeuvring qualities, HSMV can be asked to satisfy the same IMO manoeuvring requirements in calm water as for conventional ships, even if they have length less than 100 meters. Additional requirements, such as safety during fast evasive manoeuvres may be required in this case, particularly for smaller craft and those with a surface-piercing bow. For instance, smaller craft have horizontal acceleration limits during evasive manoeuvres that require a limit on engine power (Ueno et al, 1999).

The choice of sea state for manoeuvring tests depends on the type and certification of ship (some vessels are not certified for all weather). Normal operating sea state, where the ship can operate at all headings and speeds, and worst intended conditions with reduced speed must be considered.

Progress in the linear and non-linear hydrodynamic analysis of fast ships (Lin & Yue, 1990; Faltinsen & Zhao, 1991; Kring et al, 1997) allows the simulation of the wave induced motions of ships. However, a combined hydrodynamic and manoeuvring analysis without experimentally determined coefficients is still not feasible except in the preliminary phase. For accurate manoeuvring

	ITTC – Recommended Procedures	7.5 – 02 05 – 05 Page 4 of 4	
	Testing and Extrapolation Methods High Speed Marine Vehicles Manoeuvrability Evaluation and Documentation of HSMV	Effective Date 2002	Revision 01

assessment, the use of captive model tests and/or free sailing models are recommended.

3. PARAMETERS

The required parameters are the same as for conventional hull ships. Model testing poses the same requirements as for conventional ships, and should be augmented to include testing for broaching.

4. DOCUMENTATION

The same documentation is required as for conventional hull ships.

5. REFERENCES

ABS, 1997, “ABS Guide for Building and Classing High Speed Craft”.

Det Norske Veritas, 1999, “Det Norske Veritas Rules for Classification, High Speed and Light Craft”.

Faltinsen, O.M., Zhao, R., 1991, “Numerical predictions of ship motions at high forward speed”, *Phil. Trans. R. Soc. Lond. A*, 334, 241-252.

Holden, K.O., 1991, “Trial procedures for high speed marine vehicles, MARINTEK report no. 602028.00.03.

IMO, 1995, “International Code of Safety for High-Speed Craft (HSC Code)”. Resolution MSC.36 (63), adopted on May 20, 1994, IMO, London.

21st ITTC, 1996, “Report of the High-Speed Marine Vehicles Committee”, *Proceedings, Volume 1*, pp. 515-560. Bergen / Trondheim.

21st ITTC, 1996, “HSMV - Investigation of dynamic instability”, *ITTC Quality Manual*, 4.9 – 03 – 03 – 05.4.

22nd ITTC, 1999, “Manoeuvring Captive Model Test Procedure”, *ITTC Quality Manual*, 4.9 – 03 – 04 – 03

23rd ITTC, 2002, “Full Scale Manoeuvring Trials Procedure”, *ITTC Quality Manual*, 4.9 – 03 – 04 – 01.

23rd ITTC, 2002, *Quality Manual*, 2002. “Manoeuvring Free-sailing Model Test Procedure”, *ITTC Quality Manual*.

Kring, D.C., Mantzaris, D.A., Tcheou, G.B., Sclavounos, P.D., 1997, “A time-domain seakeeping simulation for fast ships”, *FAST 97*, Sydney, Australia.

Lin, W.M., Yue, D.K.P., 1990, “Numerical solutions for Large Amplitude Ship Motions in the Time Domain”, *18th Symposium on Naval Hydrodynamics*, Ann Arbor, MI., pp. 41-65.

Ueno, M., Hatate, M., Suzuki, T., Sato, K., Tanigami, A., 1999, “On engine power and manoeuvring safety of high-speed small crafts”, *5th International Conference on Fast Sea Transportation (SNAME)*, Seattle, WA.